SDS Revision Date: 10/05/2016

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity Type A Electrolyte

Alternate Names Potassium Hydroxide Solution

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee Technical Data Sheet.Application MethodSee Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Teledyne Instruments/Analytical Instruments

16830 Chestnut Street Industry, CA 91748. USA

Emergency

CHEMTREC (USA) (800) 424-9300 Customer Service: Teledyne Instruments/Analytical 626-934-1500

Instruments Technical Support: 626-934-1673

Environment, Health and Safety: 626-934-1592

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Acute Tox. 5;H303 May be harmful if swallowed. (Not adopted by US OSHA)

Skin Corr. 1A;H314 Causes severe skin burns and eye damage.

Eye Dam. 1;H318 Causes serious eye damage.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H303 May be harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

SDS Revision Date: 10/05/2016

[Prevention]:

P260 Do not breathe mist / vapors / spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P363 Wash contaminated clothing before reuse.

[Storage]:

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Potassium hydroxide. CAS Number: 0001310-58-3	10 - 25	Acute Tox. 4;H302 Skin Corr. 1A;H314	[1][2]

^[1] Substance classified with a health or environmental hazard.

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

^[2] Substance with a workplace exposure limit.

^[3] PBT-substance or vPvB-substance.

^{*}The full texts of the phrases are shown in Section 16.

SDS Revision Date: 10/05/2016

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion Do NOT induce vomiting. Rinse mouth and slowly drink several glasses of water. Call a

physician. Do NOT give anything by mouth to an unconscious or convulsing person.

4.2. Most important symptoms and effects, both acute and delayed

Overview Routes of Entry:

Inhalation: Severe irritant to lungs and respiratory tract.

Ingestion: May be fatal if swallowed.

Skin: The electrolyte (potassium hydroxide) is corrosive; skin contact may cause irritation

or severe chemical burns.

Eyes: The electrolyte (potassium hydroxide) is corrosive; eye contact may cause irritation

or severe chemicals burns.

Acute Effects: The product is harmful if swallowed, inhaled or absorbed throught the skin. This product may irritate eyes and skin on contact. It is extremely destructive to tissue of the mucous membranes, stomach, mouth, upper respiratory tract, eyes and skin. **Chronic Effects:** Prolonged exposure with the electrolyte has a destructive effect on tissue. The product is toxic to the lungs and mucous membranes. Repeated or prolonged

inhalation of vapors may lead to chronic respiratory irritation.

Signs and Symptoms of Exposure: Contact of electrolyte with skin or eyes will cause a

burning sensation and/or feel soapy or slippery to touch.

See section 2 for further details.

Eyes Causes serious eye damage.

Skin Causes severe skin burns and eye damage.

Ingestion May be harmful if swallowed. (Not adopted by US OSHA)

5. Fire-fighting measures

5.1. Extinguishing media

Use standard fire fighting media on surrounding materials including water spray, foam, and carbon dioxide. (Do not use dry chemical extinguisher containing ammonium compounds.)

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Potassium oxides

Do not breathe mist / vapors / spray.

5.3. Advice for fire-fighters

Wear NIOSH/OSHA approved self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

ERG Guide No. 154

SDS Revision Date: 10/05/2016

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Wipe down the area several times with a wet paper towel. Use a fresh towel each time. Contaminated paper towels are considered hazardous waste.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Containers should be stored in a cool, dry, well-ventilated area. Exercise due caution to prevent damage to or leakage from the container. Keep containers closed when not in use.

Incompatible materials: Highly reactive with acids. Highly corrosive in presence of aluminum. Slightly corrosive to corrosive in presence of glass.

Keep container tightly closed and dry. Keep away from incompatibles as acids and moisture. Avoid contact with skin and eyes. Do not ingest. If ingested. Seek medical advice immediately. Do not breathe fumes, vapor or spray. May corrode metallic surfaces. Store in an appropriate container. Corrosive materials should be stored in a separate safety storage cabinet or room.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0001310-58-3	Potassium hydroxide.	OSHA	No Established Limit
		ACGIH	Ceiling: 2 mg/m3
		NIOSH	C 2 mg/m3
		Supplier	No Established Limit

SDS Revision Date: 10/05/2016

Carcinogen Data

CAS No.	Ingredient	Source	Value		
0001310-58-3	Potassium hydroxide.	OSHA	Select Carcinogen: No		
		NTP	Known: No; Suspected: No		
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		

8.2. Exposure controls

Respiratory Use NIOSH/MSHA approved respirator, following manufacturer's recommendations when

concentrations exceed permissible exposure limits.

Eyes Wear safety glasses with side shields to protect the eyes. An eye wash station is

suggested as a good workplace practice.

Skin Chemical resistant clothing such as coveralls/apron boots should be worn. Wear gloves.

Gloves must be resistant to corrosive materials. Nitrile or PVC gloves are suitable. Do not

use cotton or leather gloves.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance Clear Colorless Liquid

Odor threshold Odorless

Not Measured

pH 13.5 (0.1 molar solution)

Melting point / freezing pointNot MeasuredInitial boiling point and boiling rangeNot MeasuredFlash PointNot MeasuredEvaporation rate (Ether = 1)Not MeasuredFlammability (solid, gas)Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Measured

Upper Explosive Limit: Not Measured

Vapor pressure (Pa)No Information FoundVapor DensityNo Information Found

Specific Gravity 1.1
Solubility in Water Complete

SDS Revision Date: 10/05/2016

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature

Decomposition temperature

Viscosity (cSt)

Not Measured

Not Measured

Not Measured

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Incompatible with strong oxidizers, leather and halogenated compounds. Product will react with 'soft' metals such as aluminum, tin, magnesium, and zinc releasing flammable hydrogen gas.

10.4. Conditions to avoid

Excessive heat and open flame.

Sealed containers may develop explosive pressures under fire conditions. Use water to cool containers exposed to fire.

10.5. Incompatible materials

Highly reactive with acids. Highly corrosive in presence of aluminum. Slightly corrosive to corrosive in presence of glass.

10.6. Hazardous decomposition products

Potassium oxides

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Potassium hydroxide (1310-58-3)	365.00, Rat - Category: 4	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

SDS Revision Date: 10/05/2016

Classification	Category	Hazard Description	
Acute toxicity (oral)	5	May be harmful if swallowed. (Not adopted by US OSHA)	
Acute toxicity (dermal)		Not Applicable	
Acute toxicity (inhalation)		Not Applicable	
Skin corrosion/irritation	1A	Causes severe skin burns and eye damage.	
Serious eye damage/irritation	1	Causes serious eye damage.	
Respiratory sensitization		Not Applicable	
Skin sensitization		Not Applicable	
Germ cell mutagenicity		Not Applicable	
Carcinogenicity		Not Applicable	
Reproductive toxicity		Not Applicable	
STOT-single exposure		Not Applicable	
STOT-repeated exposure		Not Applicable	
Aspiration hazard		Not Applicable	

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,
	mg/l	mg/l	mg/l
Potassium hydroxide (1310-58-3)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

SDS Revision Date: 10/05/2016

13. Disposal considerations

13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

14. Transport information

DOT (Domestic Surface

Transportation)

14.1. UN number UN1814

14.2. UN proper shipping UN1814, Potassium hydroxide,

name

solution, 8, II

14.3. Transport hazard

class(es)

DOT Hazard Class: 8

DOT Label: 8

14.4. Packing group

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

IMO / IMDG (Ocean ICAO/IATA **Transportation**)

UN1814 UN1814

Potassium hydroxide, Potassium hydroxide,

solution solution **IMDG**: 8 Air Class: 8

Sub Class: Not Applicable

Ш

Ш

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA

Inventory. **WHMIS Classification** D2B E

US EPA Tier II Hazards Fire: No.

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

Potassium hydroxide. (1,000.00)

EPCRA 302 Extremely Hazardous:

(No Product Ingredients Listed)

SDS Revision Date: 10/05/2016

EPCRA 313 Toxic Chemicals:

(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Potassium hydroxide.

Penn RTK Substances (>1%):

Potassium hydroxide.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

All chemicals may pose unknown hazards and should be used with caution. While the information contained in this Material Safety Data Sheet is believed to be correct and is offered for your information, consideration and investigation, Teledyne Analytical Instruments assumes no responsibility of the completeness or accuracy of the information contained herein.

End of Document